



Iqwa - Top Flush Suite

PRODUCT CODES

| | | |
|--------------|----------|----------------------------------|
| WHITE SUITE: | TCI408A | SUITE-IQWA TF-WHI |
| CISTERN: | CMIO8A | CISTERN-MIRAGE/IQWA TF-WHI |
| PAN: | TCIO8A | PANS-IQWA-WHI |
| SEAT: | STIQ4W08 | SEAT-IQWA WHITE (UREA) |
| MECH: | FMDFBW01 | MECH-UNIVERSAL DUAL FLUSH (WIRQ) |
| FIXATION: | EXPAN003 | FIX-PAN FIXATION KIT (L BRACKET) |

CLOSE COUPLE, CLOSED RIM, TOP FLUSH

| | |
|-------------------------|---------|
| WEIGHT OF PAN: | 26.7 kg |
| WEIGHT OF CISTERN: | 12.3 kg |
| CISTERN WATER CAPACITY: | 10 Lt |
| PAN FLUSH VOLUME: | 3/6 Lt |
| PAN WIDTH: | 365 mm |
| PAN HEIGHT: | 400 mm |
| CISTERN WIDTH: | 395 mm |
| CISTERN HEIGHT: | 382 mm |
| COMBINED HEIGHT: | 820 mm |
| INSTALLED MAX LENGTH: | 680 mm |



The Iqwa top flush is a close-couple, closed rim suite.

IQWA SUITE INSTALLATION GUIDE:

1. Fit inlet valve and flushing mechanism, as per manufacturer's instructions.
2. Attach cistern to pan using fixation bolts.
3. Fit seat, use the manufacturer's instructions.
4. Place the pan with cistern on flat (even) surface for best results.
5. Make markings on floor surface, for drilling of fixation holes (pan).
6. Remove pan and cistern, drill holes into concrete floor.
7. Slide outlet of pan onto bung of outlet pipe fitted by a qualified plumber.
8. Attach pan to floor using screw fixations.
9. Connect to the water supply.

AVAILABLE COLOURS:

