



Geberit Kombifix element for wall-hung WC, 106 cm, with Alpha concealed cistern 12 cm



Example image

Application purposes

- For masonry walls
- For installation in part or room-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For dual flush

Characteristics

- Zinc-plated installation frame
- Mounting frame with four fastening brackets
- Connection bend can be mounted without tools
- Fastening for connection bend can be mounted without tools from front
- Concealed cistern with front actuation

Scope of delivery

- Water supply connection Rp 1/2" - R 1/2", compatible with MF, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Connection set for WC, ø 90 mm
- Connection bend made of PE-HD, ø 90 mm

- Concealed cistern, fully insulated against condensation
- Immediate post flush possible with factory setting
- Water supply connection on the left or rear left
- Water supply connection, dezincification-resistant
- Protection cover box for service opening protects against moisture and dirt
- Protection box for service opening can be cut to length

Technical data

| | |
|--------------------------------------|-----------------|
| Flow pressure | 0.1-10 bar |
| Flush volume, factory setting | 6 and 3 l |
| Flush volume large, adjustment range | 4.5 / 6 / 7.5 l |
| Flush volume small, adjustment range | 3-4 l |

- Adapter socket made of PE-HD, ø 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- Fastening material

Art. no.

110.238.00.1

Accessories

- Geberit Kombifix set of leg supports
- Geberit Kombifix set of studs with foot plate