

como

True Quality is an Experience

river
luxury vinyl

Technical Data Como Earth LVT

Material:	LVT: 2mm (0.3mm wear layer)
Dimensions:	229 x 1219mm 18pcs/ctn, 60ctn/pallet, 5.02sqm
Weight per Box:	19.57kg
Weight per Pallet:	1174kg

Characteristics	Testing Procedure	Results
Wearlayer	EN 429	PASS
Usage category	RESIDENTIAL, COMMERCIAL	
Overall thickness	EN 428	PASS
Total weight / m3	EN 430	PASS
Anti static	EN1081	app 10 ¹¹ Ohm
Dimension square - and straightness	ASTM F2199	0.07%-0.13%
Height difference	ISO23999	0mm
Dimensional stability	ASTM F2199	less than 0.020"/ft
Colour fastness to artificial light	ISO 105-B02	m>6 Grade
Resistance to chemical products	ASTM F925	PASS
Toxic element test	Floorscore	ND
Castor chair	NALF A	PASS
Flexibility	EN435	Pass
Impact resistance	EN433	Pass
Reaction to fire	EN13501	Bfl-S1
Slip resistance	ASTM D 2047	>0.6
Thermal conductivity Suitable for underfloor heating	DIN 52612	0.02m ² k/w
Abration resistance	EN649	T
Sound reduction	ASTM90	STC 58 db
Emission of formaldehyd	Floorscore	ND



GLOBAL STREAM
IMPORT EXPORT
Imported and distributed by



SCAN ME
TO VISIT OUR
WEBSITE
www.globalstream.co.za