


Heavy Duty Movement Joint

The Heavy Duty Movement Joints are designed to allow for the movement in the tile panels to prevent ceramic tiles from cracking or lifting. They can be used in both medium and heavy duty applications. These products are available with a black or grey infill with other colours available on request.



Aluminium



Aluminium



Stainless Steel



Brass

Code	Height mm	Width mm	Length m
Aluminium			
HDA8	8	12	2.5
HDA10	10	12	2.5
HDA12	12	12	2.5
HDA15	15	12	2.5
HDA17	17	12	2.5
HDA225	22.5	12	2.5

Stainless Steel			
HDS8	8	12	2.5
HDS10	10	12	2.5
HDS12	12	12	2.5
HDS15	15	12	2.5
HDS17	17	12	2.5
HDS225	22.5	12	2.5

Available in grade 430, 304 and 316

Brass			
HDB8	8	12	2
HDB10	10	12	2
HDB12	12	12	2
HDB15	15	12	2
HDB17	17	12	2
HDB225	22.5	12	2

SABS Test Results		
Product	Elongation	Compression
HDA225	44.0%	33.7%
HDB225	47.4%	30.0%
HDB12	50.3%	32.8%
HDS10	69.2%	28.0%
HDA10	38.7%	33.6%
Accepted industry standard = Minimum of 20%		