

WWK 304 ZA

DHW HEAT PUMPS

PRODUCT-NO.: 203871

Become more self-sufficient at home

Self-sufficiency in your own home is an important factor. You can take a big step in the right direction with this DHW heat pump for outdoor installation. Not only does it use renewable sources for DHW heating, but with its superbly insulated cylinder, it also achieves excellent output values. For you, that means hot water for a bath or shower whenever you need it – with low energy consumption.

Easy to operate and connect

A user friendly LCD screen helps you operate the appliance. It shows you at a glance how much mixed water is currently available. What if you want to connect the heat pump to your photovoltaic system? Nothing could be simpler. The appliance comes with this option as standard, allowing you to make clever use of energy from the sun as well as the air.

The main features

DHW heat pump installed outdoors

Compact series for recirculation air mode

Hygienic DHW temperatures up to 65 °C achievable in efficient heat pump mode

Utilisation of environmental heat for energy efficient DHW heating

Highly reliable and cost saving due to the maintenance-free impressed current anode

Extremely quiet operation due to advanced acoustic separation

For supplying one or more draw-off points

Long service life and consistently high efficiency thanks to roll-bond heat exchanger

Suitable for outdoor installation at ambient temperatures of -5/+42°C

High DHW convenience through 302 l Nominal capacity





Type	WWK 304 ZA
Part no.	203871

Technical data

Energy efficiency class, DHW heating (indoor air), load profile XL	A
Average heating output (A15 / W10-55)	1,6 kW
Average heating output (A7 / W10-55)	1,2 kW
COP (EN 16147 / A20)	2,91
Nominal load profile (EN 16147)	XL
Nominal DHW temperature (EN 16147)	61 °C
Maximum available nominal amount of DHW at 40 °C (EN 16147 / A20)	457 l
Heat-up time (EN 16147 / A20)	11,17 h
Average sound pressure level at 1 m distance, free field	45 dB(A)
Sound power level (EN 12102)	60 dB(A)
Min./max. application limits, heat source for heat pump operation	-5/+42 °C
Min./max. application limits for heat source	-5/+42 °C
Max. DHW temperature with heat pump	65 °C
Min. DHW temperature with heat pump	61 °C
Height x diameter	1905 x 690 mm
Weight	135 kg
Power supply	1/N/PE 220-240 V 50/60 Hz
Safety valve connection	Rp 3/4

Nominal capacity	302 l
Max. mixed water amount at 40 °C	475 l

Energy efficiency class in accordance with EU Regulation no. 812/2013

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.