

TECHNICAL DATA

TRIBECA GRIS RECTIFICADO 80X160 cm

Glazed porcelain tiles 9,0 mm

TEST	STANDARD	REQUESTED (EN 14411)	RESULT
Dimensional characteristics	ISO 10545-2	Requested	FULFILLED
Water absorption	ISO 10545-3	Bla E<0,5%	Bla 0,1%
Modulus of rupture	ISO 10545-4	MIN 35 N/mm ²	43
Breaking strength	ISO 10545-4	MIN 1300 N	2320
Impact resistance	ISO 10545-5	---	
Abrasion resistance PEI	ISO 10545-7	Class	3
Linear thermal expansion	ISO 10545-8	---	
Thermal shock resistance	ISO 10545-9	Requested	FULFILLED
Crazing resistance	ISO 10545-11	Requested	FULFILLED
Frost resistance	ISO 10545-12	Requested	FULFILLED
Chemical resistance			
Domestic products pools aditives	ISO 10545-13	---	GA
Ácidos y alcalisAcids alkalis	ISO 10545-13	---	GLA / GHA
Stain resistance	ISO 10545-14	Min. Class 3	5
Hardness MOHS	UNE-67-101	---	6
Slip resistance (pendulum test)	UNE 41901-EX	CLASS	1
Slip resistance (ramp test - footwear)	DIN-51130		R9
Slip resistance (ramp test - barefoot)	DIN-51097		---

The test results of this sheet are made in our production plant with calibrated technology. However, we are non-official laboratory, for this reason all the results are exclusively informative and related to the tested tiles.