



Technical Specs



Mirage - Top Flush Suite

PRODUCT CODES

WHITE SUITE:	TM0408A	SUITE-MIRAGE TF-WHI
EXOTIC SUITE:	TM0410A	SUITE-MIRAGE TF-BLK
CISTERN:	CMI**A	CISTERN-MIRAGE/IQWA TF-WHI
PAN:	TM03**A	PANS-MIRAGE-**
SEAT:	STM12A**	SEAT-MIRAGE **(WOOD)
MECH:	FMDFBW01	MECH-UNIVERSAL DUAL FLUSH (WIRQ)
FIXATION:	FXPAN003	FIX-PAN FIXATION KIT (L BRACKET) SEREX

CLOSE COUPLE, OPEN RIM, TOP FLUSH

WEIGHT OF PAN:	28,3 kg
WEIGHT OF CISTERN:	12.3 kg
CISTERN WATER CAPACITY:	10 Lt
PAN FLUSH VOLUME:	3/6 Lt
PAN WIDTH:	365 mm
PAN HEIGHT:	400 mm
CISTERN WIDTH:	395 mm
CISTERN HEIGHT:	382 mm
COMBINED HEIGHT:	825 mm
INSTALLED MAX LENGTH:	665 mm



The Mirage is a top flush suite.

MIRAGE SUITE INSTALLATION GUIDE:

1. Fit inlet valve and flushing mechanism, as per manufacturer's instructions.
2. Attach cistern to pan using fixation bolts.
3. Fit seat, use the manufacturer's instructions.
4. Place the pan with cistern on flat (even) surface for best results.
5. Make markings on floor surface, for drilling of fixation holes (pan).
6. Remove pan and cistern, drill holes into concrete floor.
7. Slide outlet of pan onto bung of outlet pipe fitted by a qualified plumber.
8. Attach pan to floor using screw fixations.
9. Connect to the water supply.

AVAILABLE COLOURS:

