



Great tile treasures

MODELO/ SERIE: **SERIE LOOK**

FORMATO/SIZE: **5X50 cm**

WORK SIZE: **50 X 500 X 10,2**

MATERIAL: **REVESTIMIENTO - GRUPO BIII / WALL TILE - GROUP BIII**

<b>NORMA/ NORM</b>	<b>ABSORCION DE AGUA/ WATER ABSORPTION</b>	<b>NORMA/NORM</b>	<b>DECOCER</b>
EN ISO-10545-3		> 10%	Cumple/ Pass

  

<b>NORMA/ NORM</b>	<b>ASPECTO SUPERFICIAL/ SURFACE APPEARANCE</b>	<b>NORMA/NORM</b>	<b>DECOCER</b>
EN ISO-10545-2		>95% LIBRE DE DEFECTOS/ FREE OF DEFECTS	Cumple/ Pass

  

<b>NORMA/ NORM</b>	<b>CARACTERISTICAS DIMENSIONALES/ DIMENSIONS</b>	<b>NORMA/NORM</b>	<b>DECOCER</b>
EN ISO-10545-2	Longitud/ Lenght	$\pm 0,5\%$ / $\pm 2$ mm	Cumple/ Pass
EN ISO-10545-2	Espesor/ Thickness	$\pm 10\%$ / $\pm 0,5$ mm	Cumple/ Pass
EN ISO-10545-2	Ortogonalidad/ Orthogonality	$\pm 0,3\%$ / $\pm 2$ mm	Cumple/ Pass
EN ISO-10545-2	Curvatura/ Curvature	+ 0,5% / -0,3% // + 2,0 mm/ -1,5 mm	Cumple/ Pass
EN ISO-10545-2	Rectitud de lados / Straightness of sides	$\pm 0,3\%$ / $\pm 1,5$ mm	Cumple/ Pass

  

<b>NORMA/ NORM</b>	<b>CARACTERISTICAS QUÍMICAS/FÍSICAS / CHEMICAL/PHYSICALS CHARACTERISTICS</b>	<b>NORMA/ NORM</b>	<b>DECOCER</b>
EN ISO-10545-4	Fuerza de Rotura/ Breaking force	> 600 N	Cumple/ Pass
EN ISO-10545-4	Resistencia a la Flexión/ Flexion Resistance	> 12 N/mm <sup>2</sup>	Cumple/ Pass
EN ISO-10545-9	Choque térmico/ Thermal Shock	Cumple/ Pass	Cumple/ Pass
EN ISO-10545-11	Cuarteo/ Crazing	Cumple/ Pass	Cumple/ Pass
EN ISO-10545-13	Ácidos/Bases fuertes [H]/ Strong acids/alkalis [H]	Valor Declarado/	GHA
EN ISO-10545-13	Ácidos/Bases débiles [L] / Weak Acids/alkalis [L]	Declared value	GLA
EN ISO-10545-13	Productos domésticos y piscinas/Household and swimming poll products	min B	Cumple/ Pass
EN ISO-10545-14	Manchas/ Spots	min 3	Cumple/ Pass