

SensoWash® Starck f Shower toilet seat Plus #
 612000011401321 / 612000012000323 / 612000012400323 /
 612000012400324

|< 378 mm >|



| Shower toilet seat Plus | Dimension | Weight | Order number |
|---|--------------|----------|-----------------|
| Controllable warm air dryer steps: 4 Steps, Adjustable shower jet position level: 5 Steps, Controllable spray jet intensity steps: 3 Steps, Controllable spray jet temperature steps: 4 Steps, Adjustable shower jet position level: 5 Steps, Rearwash, Ladywash, Pulsing shower spray: Oscillating, Self-cleaning shower nozzle/shower head, Decalcification function, Energy saving mode: Adjustable, Holiday mode, Night light | | | |
| Colors | | | |
| 01 White | | | |
| Variant | | | |
| Suitable for series DuraStyle, White, Automatic close, Seat material type: Thermoplastic, Lid material type: Thermoplastic, Flow rate dryer: 12 m3/h, Warm air dryer, Seat heater, Operation type: Remote control, App, Number of programmable user profiles: 4, Odour extraction, Rated voltage: 110 V, Frequency: 60 Hz, Protection type: IPX4 | 378x218 mm | 7.000 kg | 612000011401321 |
| Suitable for series ME by Starck, White, Automatic close, Lid material type: Thermoplastic, Flow rate dryer: 12 m3/h, Warm air dryer, Seat heater, Operation type: Remote control, App, Number of programmable user profiles: 2, Odour extraction, Rated voltage: 220 - 240 V, Frequency: 50 Hz, Protection type: IPX4 | 378x218 mm | 7.000 kg | 612000012000323 |
| Suitable for series ME by Starck, White, Automatic close, Seat material type: Thermoplastic, Lid material type: Thermoplastic, Flow rate dryer: 12 m3/h, Warm air dryer, Seat heater, Operation type: Remote control, App, Number of programmable user profiles: 4, Odour extraction, Rated voltage: 220 - 240 V, Frequency: 50 Hz, Protection type: IPX4 | 378x218 mm | 7.000 kg | 612000012400323 |
| Suitable for series ME by Starck, White, Automatic close, Lid material type: Duroplast, Flow rate dryer: 12 m3/h, Warm air dryer, Seat heater, Operation type: Remote control, App, Number of programmable user profiles: 4, Odour extraction, Rated voltage: 220 - 240 V, Frequency: 50 Hz, Protection type: IPX4 | 378x218 mm | 7.000 kg | 612000012400324 |
| Installation accessories | | | |
| Pre-installation set | 135 x 105 mm | 0.43 kg | 005072 |
| Vario Connector Set Shower toilets | 220 x 60 mm | 0.28 kg | 100731 |
| Interface set | 23 x 300 mm | 0.45 kg | 100729 |

SensoWash® Starck f Shower toilet seat Plus #
 612000011401321 / 612000012000323 / 612000012400323 /
 612000012400324

|< 378 mm >|

| Suitable products | | |
|---|--------------|--------|
| Toilet wall-mounted for shower toilet seat HygieneGlaze, Flush water quantity: 4,8/4,8 l, Washdown model, Flushing rim: Rimless, Flush principle: washdown model, Outlet drain horizontal, Incl. invisible fixation, 360 x 575 mm | 360 x 575 mm | 251009 |
| One piece toilet for shower toilet seat Flush water quantity: 5/3,5 l, extractor/siphon jet, Outlet drain: vertical, Distance of rear panel/outlet: 305 mm, | | 219001 |

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.